



Representative

Catalog Number: S201-K6
UPC Number: 66201916865
EAN Number: 04016779507257
Status: Active

Miniature Circuit Breaker, Supplementary Protector, Rated Current 6 Amps, 1 Pole, Interrupt Rating 6 kA, Thermal Magnetic Trip Curve K, Voltage up to 277/Y480 VAC, 60/110 VDC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, UL 1077, CSA 22.2 No. 235

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB Provides Compact Supplementary, Energy Limiting, Circuit Protection
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Designed for Allowing Higher In-Rush Current During System Start Up; Example: Motors, Transformers
Standard	UL 1077, CSA 22.2 No. 235, IEC 60898
Voltage Rating	277/Y480 VAC, 60/110 VDC
Amperage Rating	6 Amps
Frequency Rating	50/60 Hertz
Trip Type	K
Interrupt Rating	6 kA
Number Of Poles	1
Auxiliary Contacts	Yes
Length	69 mm
Width	17.5 mm
Height	88 mm
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Inner Quantity	1
Outer Quantity	10
Outer Dimensions (inches)	7.2x3.62x3.15
Weight Uom	28.5 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com