



Representative

**Catalog Number:** S803U-K80  
**UPC Number:** 80432537234  
**Status:** Active

High Performance Miniature Circuit Breaker with Cage Terminal, Rated Current 80 Amps, 3 Pole, Trip Curve K, Voltage up to 240 VAC, Ultimate Short-Circuit Breaking Capacity 50 kA, IEC/EN 60947-2, UL 489, CSA 22.2 No. 5-02

### North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB with Cage Terminal
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Branch Circuit Protection. Designed for Use in Cable Protection Applications. Example: Control Circuits, Lighting
Standard	UL 489, IEC 60947-2, CSA 22.2 No. 5-02, cULus, E312425
Voltage Rating	240 VAC
Amperage Rating	80 Amps
Frequency Rating	50/60 Hertz
Trip Type	K
Interrupt Rating	50 kA
Number Of Poles	3
Auxiliary Contacts	Yes
Length	88.5 mm
Width	79.5 mm
Height	95 mm
Operating Temperature	-25 to +60 Degrees Celcius

### Packaging

Outer Quantity	1
Outer Dimensions (inches)	4.02x3.23x3.62
Weight Uom	1.67 lbs. Each

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
 www.tnb.com

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email:techsupport@tnb.com