



Representative

Catalog Number: SU203PR-K40
UPC Number: 80432563836
Status: Active

Miniature Circuit Breaker with Ring Tongue Terminals, Branch Circuit Protection with Ring Cable Lug, Rated Current 40 Amps, 3 Pole, Interrupt Rating 10 kA, Trip Curve K, Voltage up to 277/Y480 VAC, DIN Rail Mounted, Finger Safe and Multi-Function Terminals, UL 489, CSA 22.2 No. 5

North American Specifications (UNSPSC)

UNSPSC	39121603 Miniature circuit breakers
IGCC	4897 Miniature circuit breakers
Brand Name	ABB
Type	High Performance MCB with Ring Tongue Terminal
Special Features	DIN Rail Mounting, Finger Safe and Multi-Function Terminals
Application	Designed for Allowing Higher In-Rush Current During System Start Up; Example: Motors, Transformers
Standard	UL 489, CSA 22.2 No. 5, IEC 60947-2, UL E212323
Voltage Rating	277/Y480 VAC
Amperage Rating	40 Amps
Frequency Rating	50/60 Hertz
Trip Type	K
Interrupt Rating	10 kA
Number Of Poles	3
Auxiliary Contacts	Yes
Length	69 mm
Width	52.5 mm
Height	115 mm
Operating Temperature	-25 to +55 Degrees Celcius

Packaging

Outer Quantity	3
Outer Dimensions (inches)	7.6x4.7x3.3
Weight Uom	79.06 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com