

XT4NU2050AFF000XXX 88861440803

Active

Tmax Breaker Frame Size XT4N 250 Thermal Magnetic Fixed 50-500 Two-Pole Fixed + Front Flat Terminals Underwriters Laboratory/Canadian Standards Association

North American Specifications (UNSPSC)
--

North American opecificat				
UNSPSC	39121616 Molded case circuit breakers			
IGCC	4927 Molded case circuit breakers			
Brand Name	ABB			
Sub Brand	Tmax XT			
Туре	Molded case circuit breaker			
Special Features	Feature high specific let-trhough current peak and			
	energy limiting characteristics that allow the ciruits			
	and equipment on the load side to be sized in Opti-			
	mum way.			
Application	Ideal solution for all distribution levels from the main			
	low voltage sweitchboard to the subswtichboards in			
	the installatin			
Standard	UL 80% rated / IEC dual rated			
Frame	XT4 - to 250A, 600V (UL) / 250A, 690V (IEC) -			
	Thermal magnetic and Electronic protection			
Trip Type	Thermal magnetic fixed (TMF)			
Number Of Poles	2 Poles			
Packaging				
Outer Quantity	1			
Outer Dimensions (inches)	6.6 <mark>1</mark> x5.71x8.27			

5.51 lbs. Each

Weight Uom

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com

Thomas&Betts