


Control Circuit and Load Protection Products

Bulletin Numbers 188, 1489, 1492, 1692



**LISTEN.
THINK.
SOLVE.**


Circuit Protection Portfolio



1489-M Circuit Breakers
Approved for branch circuit protection in the United States and Canada, and certified as Miniature Circuit Breakers for IEC applications.



1492-SP Supplementary Protectors
Overcurrent protection for equipment where branch circuit protection is already provided, or is not required. Also Miniature Circuit Breakers as defined by IEC Standards.



1492-D Circuit Breakers
Overcurrent and short circuit protection for higher voltage DC circuits. Also Miniature Circuit Breakers as defined by IEC Standards.



188-J 10 kA Regional Circuit Breakers
Protective devices applied at the equipment level. Regional certifications only. Available for purchase in China and Europe.



188-K 6 kA Regional Circuit Breakers
Protective devices applied at the equipment level. Regional certifications only. Available for purchase in China and Europe.

Rockwell Automation offers a wide range of Allen-Bradley circuit protection products designed for a variety of applications.

Miniature Circuit Breakers, Supplementary Protectors, and Residual Current Devices

Product	Certifications						Poles						Trip			Trip Current [A]								
	cULus	cURus	CSA	CE	VDE	CCC	1	1+N	2	3	3+N	4	B	C	D	0.2	0.5	0.8	1	1.2	1.5	1.6	2	2.5
1489-M	●		●	●	●	●	●		●	●				●	●				●				●	●
1492-SP		★	●	●	●	●	●	♣	●	●	♣		●	●	●				●				●	●
1492-D		★	●	●	●		●		●					●					●				●	●
188-J,-K				●	●	●	●	●	●	●	●		●	●	●				●					●
1492-RCD		●		●	●	●			●		●													
1492-MC	●		●				●		●	●														
1492-GH,-GS		●	●	●	●		●		●	●						●	●	●	●	●	●	●	●	●

★ UL Recognized only.
♣ 1+N and 3+N devices are not cURus or CSA certified.

Electronic Circuit Protectors

Product	Certifications				Circuits		Output Current Rating [A]									
	cULus	CE	C1D2	NEC C2	4	2x2	1	2	3	4	6	10	3/6	6/12		
1692	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	



**1492-RCD
Residual Current
Devices**

By detecting small leakage currents and disconnecting all ungrounded connectors quickly, RCDs can prevent injury to exposed personnel and damage to equipment.



**1692 Electronic
Circuit Protectors**

Protection for secondary circuits of 24V DC switched mode power supplies. These modules monitor both supply voltage and load currents, and can be monitored and controlled locally and remotely.



**1492-MC Circuit
Breakers and Ground
Fault Protectors**

Thermal magnetic circuit protection and sensing thresholds for personnel and equipment protection.



**1492-GH, -GS High-density
Supplementary
Protectors**

Thermal magnetic circuit breakers with a high density design useful when DIN Rail space is a premium.



1492-FB Fuse Holders

Designed for use in many OEM applications. Provides safe and convenient installation of Midget, Class CC, and Class J fuses.

- Test equipment
- Automotive systems
- Controller I/O points
- Power supplies

- Relay and contractor coils
- Medical equipment
- Control instrumentation

- Computers
- Solenoids
- Transformers

Rated Current [A]																									
3	4	5	6	7	8	10	12	13	15	16	20	25	30	32	35	40	45	50	55	60	63	70	80	90	100
●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●		●		●	●				
●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●		●		●	●				
●	●		●		●	●		●		●	●	●	●	●	●	●		●		●	●				
●	●		●		●	●		●		●	●	●	●	●	●	●		●		●	●				
						●				●	●	●	●	●	●	●		●		●	●		●	●	●
●	●	●	●	●	●	●	●		●	●	●	●					●	●	●	●	●	●	●	●	●

Typical North America Current Ratings: 0.5, 1, 2, 3, 4, 5, 6, 7, 8, 10, 15, 20, 25, 30, 40, 50, 60, 63 A.
 Typical IEC Current Ratings: 0.5, 1, 1.6, 2, 3, 4, 6, 8, 10, 13, 16, 20, 25, 32, 40, 50, 63 A.

Fuse Holders

Product	Certifications			Poles			Indication			Fuse Types			
	cULus	CSA	CE	1	2	3	none	L	D1	M30	C30	J30	J60
1492-FB	●	●	●	●	●	●	●	●	●	●	●	●	●