

Control and Load Switch Specifications

Bulletin Number 194E, 194L

Topic	Page
Product Line Overview	2
194E General Specifications	3
194E Approximate Dimensions	5
194L Circuit Diagrams	13
194L General Specifications	17
Approximate Dimensions	20

Additional Resources

These documents contain additional information concerning related products from Rockwell Automation.

Resource	Description
Industrial Automation Wiring and Grounding Guidelines, publication 1770-4.1	Provides general guidelines for installing a Rockwell Automation industrial system.
Product Certifications website, http://www.ab.com	Provides declarations of conformity, certificates, and other certification details.

You can view or download publications at <http://www.rockwellautomation.com/literature/>. To order paper copies of technical documentation, contact your local Allen-Bradley distributor or Rockwell Automation sales representative.

			
	Bulletin 194E	Bulletin 194L	
Product Type	Inductive load-rated load switch		Inductive load-rated control/load switch
Current Range	16...100 A		12...40 A
Main Applications	UL, CSA ratings "suitable as at-motor disconnect"		UL, CSA ratings "suitable as at-motor disconnect"
Functionality	3- or 6-pole switch configurations for OFF-ON or changeover applications (16...100 A switches)		1- to 6-pole multifunction switch control configurations for OFF-ON, changeover, Star-Delta (Wye-Delta), reversing, ammeter, voltmeter, and step switch applications - Also available in custom control configurations up to 16 circuits for any unique control switching application.
Mounting Styles	Front/door or base/DIN Rail mounting		Front/door or base/DIN Rail mounting
Handles	- Handle colors in grey/black and red/yellow and padlockable versions - Legend plates available in 0-I international markings and text styles		- Uniformly styled handles: selector knob, disk style, rectangular style, and key-operated versions (Type 1/12, IP66) - Handle colors in grey/black and red/yellow and padlockable versions - Legend plates available in 0-I international markings and text styles
Open Switch or Enclosed	- Open switch (large frame Bul. 194E — open style only) - Enclosed: IP66 thermoplastic enclosure or UL/CSA rated enclosure		Open switch
UL/CSA Electrical Ratings:			
Rated Voltage U_e	600V AC		600V AC
Rated Current I_e	16...100 A @ 600V		12...40 A @ 600V
Rated Power P_e [FLA]	Varies w/ 1- or 3-phase switch, voltage		Varies w/ 1- or 3-phase switch, voltage
Short-Circuit Ratings	5 kA		5 kA
Switching Rate [ops/h]	120		120
Mechanical Life [ops]	0.2 million (16...100 A switches)		1 million
IEC Rated Current I_e			
AC-1	16...100 A @ 600V		12...40 A @ 600V
AC-21A	16...100 A @ 600V		12...40 A @ 600V
AC-22A	16...100 A @ 600V		12...40 A @ 600V
Ambient Operational Temp.	-25...+60 °C (-13...+140 °F)		-25...+60 °C (-13...+140 °F)
Ambient Enclosed Temp.	-20...+60 °C (-4...+140 °F)		-20...+60 °C (-4...+140 °F)
Ambient Storage Temp.	-40...+80 °C (-40...+176 °F)		-40...+80 °C (-40...+176 °F)
Protection class per IEC 529	Switch bodies: IP2		Switch bodies: IP2
Optional Accessories	- IP66 handles - Multi-length shafts and shaft extension kits - Terminal covers		- Multi-length shafts and shaft extension kits - Terminal covers
Standards/Certifications	- UL 508 - CSA C22.2, No. 14 - IEC 60947-3 Low Voltage Switchgear and Controlgear part 3 - CE		- UL 508 - CSA C22.2, No. 14 - IEC 60947-3 Low Voltage Switchgear and Controlgear part 3 - CE

Electrical Ratings

Performance Data				16 A	25 A	32 A	40 A	63 A	80 A	100 A	Aux. Contacts		
IEC Applications													
Rated operational voltage (U_e): IEC ★				[V]	690	690	690	690	690	690	690		
Rated operational voltage (U_e): UL, CSA				[V]	600	600	600	600	600	600	600		
Rated isolation voltage (U_i): IEC/UL, CSA				[V]	690/600	690/600	690/600	690/600	690/600	690/600	690/600		
Rated impulse voltage (U_{imp}): UL, CSA				[kV]	8	8	8	8	8	8	8		
Test voltage, (U_i) 1 minute				[kV]	2.5	2.5	2.5	2.5	2.5	2.5	2.5		
Lost power per pole				[W]	0.58	1.0	1.5	1.6	2.4	3.6	5.5		
Rated frequency				[Hz]	50/60	50/60	50/60	50/60	50/60	50/60	50/60		
Conventional free air thermal current I_{th} ★				[A]	25	40	50	63	75	100	120		
Conventional enclosed thermal current I_e ★				[A]	20	32	40	50	63	80	100		
Rated current I_e ★													
AC-1/	Non-inductive or only slightly inductive loads			[A]	16	25	32	40	63	80	100		
AC-21A	Switching of resistive loads with slight overload												
Rated power P_e													
AC-23A	Occasional switching of 3Ø motors and other highly inductive loads (criterion for selecting main switches)	230V	[kW]	5.5	7.5	7.5	15	18.5	22	30	—		
		400V	[kW]	7.5	11	15	22	30	37	55	—		
		690V	[kW]	7.5	11	15	18.5	22	37	45	—		
AC-3	Squirrel-cage motors; starting and stopping of running motors	230V	[kW]	4	5.5	7.5	11	15	18.5	22	—		
		400V	[kW]	5.5	7.5	11	15	18.5	30	37	—		
		690V	[kW]	5.5	7.5	11	15	18.5	30	22	—		
Short circuit current (co-ordination type 2)			[kA]	20	20	15	20	15	30	25	—		
			[A]	20	25	35	50	63	80	100	—		
			[A]	800	900	900	1300	1300	2500	2500	—		
Rated breaking capacity AC23A (cosφ 0.45)		230V	[A]	156	296	296	484	484	780	780	—		
		400V	[A]	120	256	256	504	504	800	800	—		
		690V	[A]	70	136	136	196	196	376	376	—		
DC switching capacity													
Rated current I_e	1 pole	24/48V	[A]	20	25	32	40	63	80	100	—		
		110V	[A]	5	5	6	8	10	16	20			
		220V	[A]	1	1	1	1.5	15	3	3			
		440V	[A]	0.5	0.5	0.5	0.6	0.6	0.7	0.7			
DC-21A	2 poles in series	96V	[A]	20	25	32	40	63	80	100	—		
		110V	[A]	20	23	25	32	50	70	80			
		220V	[A]	5	5	6	8	10	16	20			
		440V	[A]	1	1	1	1.5	1.5	3	3			
	3 poles in series	600V	[A]	0.6	0.6	0.6	0.8	0.8	1	1	—		
		110V	[A]	20	25	32	40	63	80	100			
		220V	[A]	13	13	15	20	28	50	63			
		440V	[A]	2.2	2.2	2.2	3.6	3.6	6.5	6.5			
		600V	[A]	1.3	1.5	1.5	2	2	3	3			
Rated power P_e													
DC-23A, DC-3, DC-5	3 poles in series	90V	[kW]	1	1.3	1.5	2.9	4.1	5.1	7.2	—		
			For inductive loads, T ≤ 15 ms	110V	[kW]	1	1.1	1.3	2.2	3.3		5.5	7
		220V	[kW]	0.8	0.9	1.1	1.7	2	3.5	4.4			
		440V	[kW]	0.6	0.6	0.6	0.9	0.9	1.1	1.1			
		600V	[kW]	0.4	0.4	0.4	0.5	0.5	0.9	0.9			

★ See standards compliance listed on <http://ab.rockwellautomation.com/Circuit-and-Load-Protection/Disconnect-Switches/Non-Visible-Blade/194R-Fused-Non-Fused-Disconnect-Switches#specifications>