

# General Purpose Enclosure Specifications

Bulletin Number 598

Topic	Page
Specifications	2

## Additional Resources

These documents contain additional information concerning related products from Rockwell Automation.

Resource	Description
Industrial Automation Wiring and Grounding Guidelines, publication <a href="#">1770-4.1</a>	Provides general guidelines for installing a Rockwell Automation industrial system.
Product Certifications website, <a href="http://www.ab.com">http://www.ab.com</a>	Provides declarations of conformity, certificates, and other certification details.

You can view or download publications at <http://www.rockwellautomation.com/literature/>. To order paper copies of technical documentation, contact your local Allen-Bradley distributor or Rockwell Automation sales representative.



Bulletin	598	598																																		
<b>Description</b>	<b>General-Purpose Enclosure</b>	<b>Junction Box</b>																																		
<b>Features</b>	Designed for use as an automation control box, electrical control housing, and terminal wiring box in industrial and commercial applications	Designed for use as a junction box, terminal wiring box, and small automation control box in industrial and commercial applications																																		
<b>Approximate Dimensions and Shipping Weights</b>	Available in 11 sizes (Height x Width x Depth) <table border="0"> <tr><td>130 x 80 x 85 mm</td><td>271 g (0.60 lb)</td></tr> <tr><td>180 x 80 x 85 mm</td><td>357 g (0.79 lb)</td></tr> <tr><td>250 x 80 x 85 mm</td><td>435 g (0.96 lb)</td></tr> <tr><td>190 x 190 x 130 mm</td><td>802 g (1.77 lb)</td></tr> <tr><td>280 x 190 x 130 mm</td><td>1261 g (2.78 lb)</td></tr> <tr><td>280 x 280 x 130 mm</td><td>1308 g (2.88 lb)</td></tr> <tr><td>340 x 280 x 130 mm</td><td>1643 g (3.62 lb)</td></tr> <tr><td>380 x 190 x 180 mm</td><td>1685 g (3.71 lb)</td></tr> <tr><td>380 x 280 x 180 mm</td><td>2069 g (4.56 lb)</td></tr> <tr><td>560 x 280 x 130 mm</td><td>2622 g (5.78 lb)</td></tr> <tr><td>560 x 380 x 180 mm</td><td>4327 g (9.54 lb)</td></tr> </table>	130 x 80 x 85 mm	271 g (0.60 lb)	180 x 80 x 85 mm	357 g (0.79 lb)	250 x 80 x 85 mm	435 g (0.96 lb)	190 x 190 x 130 mm	802 g (1.77 lb)	280 x 190 x 130 mm	1261 g (2.78 lb)	280 x 280 x 130 mm	1308 g (2.88 lb)	340 x 280 x 130 mm	1643 g (3.62 lb)	380 x 190 x 180 mm	1685 g (3.71 lb)	380 x 280 x 180 mm	2069 g (4.56 lb)	560 x 280 x 130 mm	2622 g (5.78 lb)	560 x 380 x 180 mm	4327 g (9.54 lb)	Available in 6 sizes (Height x Width x Depth) <table border="0"> <tr><td>90 x 70 x 50 mm</td><td>103 g (0.23 lb)</td></tr> <tr><td>165 x 85 x 50 mm</td><td>189 g (0.42 lb)</td></tr> <tr><td>130 x 80 x 85 mm</td><td>271 g (0.60 lb)</td></tr> <tr><td>180 x 80 x 85 mm</td><td>357 g (0.79 lb)</td></tr> <tr><td>250 x 80 x 85 mm</td><td>435 g (0.96 lb)</td></tr> <tr><td>190 x 190 x 130 mm</td><td>802 g (1.77 lb)</td></tr> </table>	90 x 70 x 50 mm	103 g (0.23 lb)	165 x 85 x 50 mm	189 g (0.42 lb)	130 x 80 x 85 mm	271 g (0.60 lb)	180 x 80 x 85 mm	357 g (0.79 lb)	250 x 80 x 85 mm	435 g (0.96 lb)	190 x 190 x 130 mm	802 g (1.77 lb)
130 x 80 x 85 mm	271 g (0.60 lb)																																			
180 x 80 x 85 mm	357 g (0.79 lb)																																			
250 x 80 x 85 mm	435 g (0.96 lb)																																			
190 x 190 x 130 mm	802 g (1.77 lb)																																			
280 x 190 x 130 mm	1261 g (2.78 lb)																																			
280 x 280 x 130 mm	1308 g (2.88 lb)																																			
340 x 280 x 130 mm	1643 g (3.62 lb)																																			
380 x 190 x 180 mm	1685 g (3.71 lb)																																			
380 x 280 x 180 mm	2069 g (4.56 lb)																																			
560 x 280 x 130 mm	2622 g (5.78 lb)																																			
560 x 380 x 180 mm	4327 g (9.54 lb)																																			
90 x 70 x 50 mm	103 g (0.23 lb)																																			
165 x 85 x 50 mm	189 g (0.42 lb)																																			
130 x 80 x 85 mm	271 g (0.60 lb)																																			
180 x 80 x 85 mm	357 g (0.79 lb)																																			
250 x 80 x 85 mm	435 g (0.96 lb)																																			
190 x 190 x 130 mm	802 g (1.77 lb)																																			
<b>Degree of Protection</b>	Type 1, 3R, 4, 4X, 12, 13 IP66 Indoor/Outdoor	Type 1, 3R, 4, 4X, 12, 13 IP66 Indoor/Outdoor																																		
<b>Storage Temperature Range</b>	-40...+75 °C (-40...+158 °F)	-40...+75 °C (-40...+158 °F)																																		
<b>Operating Temperature Range</b>	-40...+55 °C (-40...+131 °F)	-40...+55 °C (-40...+131 °F)																																		
<b>Material</b>																																				
<b>Enclosure — Solid Base and Cover</b>	Thermoplastic polyester blend, UL94-5VA	Thermoplastic polyester blend, UL94-5VA																																		
<b>Enclosure — Clear Cover</b>	Polycarbonate, UL94-5VA	Polycarbonate, UL94-5VA																																		
<b>Gasket</b>	Foam-in-place polyurethane	Foam-in-place polyurethane																																		
<b>Plastic Mounting Plate</b>	ABS	ABS																																		
<b>Metal Mounting Plate</b>	Steel plus zinc with chromate plating	Steel plus zinc with chromate plating																																		
<b>Mounting Plate Hardware (included with enclosure)</b>	Stainless steel	Stainless steel																																		
<b>Mounting Provision</b>	Brass	Brass																																		
<b>External Mounting Bracket</b>	Stainless steel	Stainless steel																																		
<b>Hinges and Latches</b>	Stainless steel	Stainless steel																																		
<b>Cover Screw</b>	Glass-reinforced nylon	Glass-reinforced nylon or stainless steel																																		
<b>Cover Plug (for hinged enclosures only)</b>	Polypropylene	—																																		

## Important User Information

Read this document and the documents listed in the additional resources section about installation, configuration, and operation of this equipment before you install, configure, operate, or maintain this product. Users are required to familiarize themselves with installation and wiring instructions in addition to requirements of all applicable codes, laws, and standards.

Activities including installation, adjustments, putting into service, use, assembly, disassembly, and maintenance are required to be carried out by suitably trained personnel in accordance with applicable code of practice.

If this equipment is used in a manner not specified by the manufacturer, the protection provided by the equipment may be impaired.

In no event will Rockwell Automation, Inc. be responsible or liable for indirect or consequential damages resulting from the use or application of this equipment.

The examples and diagrams in this manual are included solely for illustrative purposes. Because of the many variables and requirements associated with any particular installation, Rockwell Automation, Inc. cannot assume responsibility or liability for actual use based on the examples and diagrams.

No patent liability is assumed by Rockwell Automation, Inc. with respect to use of information, circuits, equipment, or software described in this manual.

Reproduction of the contents of this manual, in whole or in part, without written permission of Rockwell Automation, Inc., is prohibited.

## Documentation Feedback

Your comments will help us serve your documentation needs better. If you have any suggestions on how to improve this document, complete this form, publication [RA-DU002](#), available at <http://www.rockwellautomation.com/literature/>.

Allen-Bradley, Rockwell Software, Rockwell Automation, and LISTEN. THINK. SOLVE are trademarks of Rockwell Automation, Inc.  
Trademarks not belonging to Rockwell Automation are property of their respective companies.

Rockwell Otomasyon Ticaret A.Ş., Kar Plaza İş Merkezi E Blok Kat:6 34752 İçerenköy, İstanbul, Tel: +90 (216) 5698400

**[www.rockwellautomation.com](http://www.rockwellautomation.com)**

### Power, Control and Information Solutions Headquarters

Americas: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444  
Europe/Middle East/Africa: Rockwell Automation NV, Pegasus Park, De Kleetlaan 12a, 1831 Diegem, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640  
Asia Pacific: Rockwell Automation, Level 14, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846