

03643

FRONT PLATE VIGI NSX.TOGGLE / CVS.ROTARY - 3P 630A HORIZONTAL WIDTH650 3MODULES



Main

Range	Prisma
Range compatibility	Prisma P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Type of front plate	Cut-out
Installed device	Compact: fixed NSX400 without earth leakage protection - control: toggle - horizontal installation Compact: fixed NSX630 without earth leakage protection - control: toggle - horizontal installation Easypact: fixed CVS400 without earth leakage protection - control: direct front rotary handle - horizontal installation Easypact: fixed CVS630 without earth leakage protection - control: direct front rotary handle - horizontal installation Compact: plug-in NSX400 without earth leakage protection - control: toggle - horizontal installation Compact: fixed NSX400 without earth leakage protection - control: direct front rotary handle - horizontal installation Compact: fixed NSX400 without earth leakage protection - control: motor mechanism - horizontal installation Compact: plug-in NSX400 without earth leakage protection - control: direct front rotary handle - horizontal installation Compact: plug-in NSX400 without earth leakage protection - control: motor mechanism - horizontal installation Compact: plug-in NSX630 without earth leakage protection - control: toggle - horizontal installation Compact: fixed NSX630 without earth leakage protection - control: direct front rotary handle - horizontal installation Compact: fixed NSX630 without earth leakage protection - control: motor mechanism - horizontal installation Compact: plug-in NSX630 without earth leakage protection - control: direct front rotary handle - horizontal installation Compact: plug-in NSX630 without earth leakage protection - control: motor mechanism - horizontal installation Easypact: fixed CVS400 with earth leakage protection - control: direct front rotary handle - horizontal installation Easypact: fixed CVS630 with earth leakage protection - control: direct front rotary handle - horizontal installation Compact: fixed NSX400 with earth leakage protection - control: toggle - horizontal installation

Compact: plug-in NSX400 with earth leakage protection - control: toggle - horizontal installation
 Compact: fixed NSX400 with earth leakage protection - control: direct front rotary handle - horizontal installation
 Compact: fixed NSX400 with earth leakage protection - control: motor mechanism - horizontal installation
 Compact: plug-in NSX400 with earth leakage protection - control: direct front rotary handle - horizontal installation
 Compact: plug-in NSX400 with earth leakage protection - control: motor mechanism - horizontal installation
 Compact: fixed NSX630 with earth leakage protection - control: toggle - horizontal installation
 Compact: plug-in NSX630 with earth leakage protection - control: toggle - horizontal installation
 Compact: fixed NSX630 with earth leakage protection - control: direct front rotary handle - horizontal installation
 Compact: fixed NSX630 with earth leakage protection - control: motor mechanism - horizontal installation
 Compact: plug-in NSX630 with earth leakage protection - control: direct front rotary handle - horizontal installation
 Compact: plug-in NSX630 with earth leakage protection - control: motor mechanism - horizontal installation

Poles description	1 x 3P: mounting plate support: CVS400 horizontal installation 1 x 3P: mounting plate support: CVS630 horizontal installation 1 x 3P: mounting plate support: NSX400 horizontal installation 1 x 3P: mounting plate support: NSX630 horizontal installation
Operating position	Horizontal

Complementary

Enclosure/Cubicle description	Cubicle - width 650 mm depth 400 mm
Connection position	Direct connection
Number of vertical modules [50 mm]	4
Standards	IEC 61439-2 IEC 61439-1
Product certifications	ASEFA
Quantity per set	Set of 1
Height	200 mm
Net weight	0.74 kg
Surface finish	Matt Smooth
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9001)

Environment

IK degree of protection	IK07 conforming to EN/IEC 62262
-------------------------	---------------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	750 g
Package 1 Height	2.6 cm
Package 1 width	21 cm
Package 1 Length	51 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Weight	7.65 kg
Package 2 Height	17 cm
Package 2 width	22.5 cm
Package 2 Length	53 cm
Unit Type of Package 3	P12
Number of Units in Package 3	90
Package 3 Weight	81.6 kg

Package 3 Height	36 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

