



Main

Product range	Minera
Product or component type	Oil type transformer
Dielectric liquid	Mineral oil
Network type	AC
Standards	IS 1180
Type of installation	Indoor/outdoor
Maximum altitude	< 1000 m
Cooling mode	ONAN (oil natural air natural)
Winding material	Copper
Degree of protection	IP00 conventional IS 2099 IP00 conventional IS 3347 IP55 low voltage cable box
Mounting mode	Ground mounted

Complementary

Phase	3 phases
Rated power	2500 kVA
Rated frequency	50 Hz
Rated primary voltage	33 kV
Secondary voltage (at no-load)	Operation/loading as per IS standard: 433 V
Rated insulation level	Primary circuit: 70 kV AC Secondary circuit: 3 kV AC
Insulation voltage to industrial frequency (50 Hz 1 mn)	36 kV AC primary 1.0 kV AC secondary
Lighting impulse withstand voltage (BIL) , 1.2/50 µs	170 kV
Vector group	Dyn11
HV tapings (off circuit)	- 15...5 x 2.5 %
Short circuit impedance	6.25 %
Temperature rise of windings	40/45 K (oil and winding insulation)

Thermal class	A
Electrical connection	Cable box high voltage connection Bus duct low voltage connection
Protective relay	OTI relay WTI relay BR relay PRV relay
Height	2750 mm
Width	3250 mm
Length	4150 mm
Total weight	9350 kg

Environment

Maximum ambient temperature	50 °C
Ambient air temperature for operation	-6...50 °C
Ambient air temperature for storage	-6...50 °C
Environmental certification	0...95 %
Fire certificate	Level 1

Packing Units

Package 1 Weight	9650.000 kg
Package 1 Height	3100.000 mm
Package 1 width	3300.000 mm
Package 1 Length	4500.000 mm

