Product data sheet Characteristics

NSYCRN64150P

Spacial CRN plain door with mount.plate. H600xW400xD150 IP66 IK10 RAL7035...





Main

IVIAIII		
Range	Spacial	
Product name	Spacial CRN	
Application	Multi-purpose	
Category	Compact enclosure	
Enclosure nominal height	600 mm	
Enclosure nominal width	400 mm	<u></u>
Enclosure nominal depth	150 mm	<u>.</u>
Installation accessory type	Wall-mounting	
Device composition	1 body 1 cable gland plate 1 door with lock 1 mounting plate	i iono
Door type	Plain	
Mounting plate description	Plain	

Complementary

Body type	Back welded with double profile forming a protected sealed area Sides made from a single folded section	
Number of doors	Front face: 1 door(s)	-
Door opening side	Reversible (120 °)	
Lock type	3 mm double-bar lock	
Type of gland plate	Standard	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	:
Material	Enclosure: steel Mounting plate: galvanised steel	- - !

Surface finish	Enclosure: epoxy-polyester powder		
Colour	Enclosure: grey (RAL 7035)		
Standards	IEC 62208		
Product certifications	CUL UL		
Net weight	11.69 kg		

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	11.69 kg
Package 1 Height	62 cm
Package 1 width	42 cm
Package 1 Length	17 cm

Offer Sustainability

Sustainable offer status	Green Premium product Yes			
REACh free of SVHC				
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration			
Mercury free	Yes			
RoHS exemption information	Yes			
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information			
Environmental Disclosure Product Environmental Profile				

Contractual warranty

Contractadi Warranty			
Warranty	18 months		