## Product data sheet Characteristics

# NSYS3D6625T

Spacial S3D tspt door w/o mount.plate H600xW600xD250.IP66 IK08 RAL7035.





#### Main

IVIAIII	
Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	600 mm
Enclosure nominal width	600 mm
Enclosure nominal depth	250 mm
Door type	Glazed
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 1 lock
	1 cable gland plate

## Complementary

Body type	Single piece body Gutter-shaped front rail double sheet thickness	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws	:
Material	Body: steel Door: steel and security glass	
Surface finish Epoxy-polyester powder		

Colour	Grey (RAL 7035)
Standards	IEC 62208
Product certifications	GL
	BV
	DNV
	LR
	UL
	CUL
Net weight	15.9 kg

#### Environment

Electromagnetic compatibility	Electromagnetic field immunity test	
IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK08 conforming to IEC 62262	

#### **Packing Units**

Package 1 Weight	15.900 kg	
Package 1 Height	613.000 mm	
Package 1 width	618.000 mm	
Package 1 Length	298.000 mm	

## Offer Sustainability

Sustainable offer status	Green Premium product			
REACh free of SVHC	Yes			
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration			
Mercury free	Yes			
RoHS exemption information	Yes			
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information			
Environmental Disclosure	Product Environmental Profile			

#### Contractual warranty

Warranty	18 months		