Product data sheet Characteristics

NSYSF201040T

Spacial SF enclosure glazed door - assembled - 2000x1000x400 mm







Spacial	
Spacial SF	
Multi-purpose	
Suitable enclosure	
2000 mm	
1000 mm	
400 mm	
Floor-standing	
Floor-standing 2 sliding rails 4 mounting plate bracket 1 structure 1 door 1 locking system with handle: door 1 rear panel 1 roof	

Complementary

· · · · · · · · · · · · · · · · · ·		•
Structure type	Formed from a single section Vertical uprights joined with top and bottom frames Panels and doors built into the structure Perforated structure with a pitch of 25 mm	
Door type	Glazed front	
Number of doors	Front: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	4 points lock, handle with 5 mm double bar insert front door	
Mounting plate description	Without mounting plate	
Type of gland plate	Without gland plate	
Accessibility for operation	Sides of enclosure Front Rear	, F
		-

Removable parts	Door by screws hinge Rear panel by screws Roof by screws Mounting plate bracket by screws Sliding rail by screws
Material	Frame: galvanised steel Uprights: galvanised steel Door: Securit glass Door: sheet steel Panels: sheet steel Hinge: zamak Handle: polyamide 6 with 30 % fibre glass
Surface finish	Epoxy-polyester powder
Colour	Enclosure: grey (RAL 7035) Handle: black (RAL 9005)
Net weight	121.9 kg

Environment

Standards	IEC 62208
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262

Packing Units

r dorang ornito		
Package 1 Weight	121.900 kg	
Package 1 Height	2130.000 mm	
Package 1 width	1045.000 mm	
Package 1 Length	490.000 mm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty 18	8 months