



Main

Range	Exiway
Product name	Exiway Easyled
Product or component type	Emergency light fitting
Function	Standard
Supply	Maintained Non-maintained
Number of batteries	1 x 3.6 V 1.6 Ah Ni-Cd (Nickel-Cadmium)
Light source	LED integral LED 4 x 0.5 W
Wiring device additional information	Can be inhibited with rest mode via Teleur range of remote controls

Complementary

Range compatibility	remote control
[Ue] rated operational voltage	230 V 50/60 Hz
Power consumption in VA	3.7 VA non-maintained 5.3 VA maintained
Power consumption in W	0.9 W non-maintained 2.3 W maintained
Electrical insulation class	Class II
Autonomy	3 h
Charging time	24 h
Luminous flux	Emergency condition: 105 lm Maintained mode: 55 lm
Type of glass	Serigraphed transparent glass
Device mounting	Surface ceiling Flush false ceiling Flush wall Surface wall
Height	116 mm
Width	292 mm
Depth	37 mm
Net weight	0.53 kg

Environment

IP degree of protection	IP65
IK degree of protection	IK07
Ambient air temperature for operation	0...40 °C
Fire resistance	850 °C
Product certifications	ENEC
Standards	EN/IEC 60598-2-22 IEC 60695-2-10

Packing Units

Package 1 Weight	515.000 g
Package 1 Height	38.000 mm
Package 1 width	117.000 mm
Package 1 Length	293.000 mm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information