



## Main

Range of product	Easergy P5
Product or component type	Protection relay
Relay application	Feeder - directional over current
Product reference	P5F30-AACB-HABAH-AAAA
Mounting case size	30TE
Device mounting	Flush
Mounting mode	Withdrawable
Power supply	48...250 V DC 100...230 V AC
Measuring inputs	: 1/5 A CT phase current 3 : CSH residual current 1 : VT voltage 4
Number of sensors	0 temperature sensor(s) 0 arc sensor(s)
Number of Digital Inputs (DI)	10
Number of Digital Outputs (DO)	7 DO 1 watchdog
Number of analogue inputs	0
Number of analogue outputs	0
Communication ports	RJ45 2 rear Extension port 1 rear with backup memory USB port 2 front
Communication protocols	IEC 61850 ed. 1 IEC 61850 ed. 2 DNP3 over ethernet Modbus TCP Ethernet/IP
Redundancy communication port protocol	RSTP
Cybersecurity	Password protection Port hardening
Protection functions	Phase overcurrent 50/51 Directional phase overcurrent 67 Earth fault overcurrent 50N/51N Directional earth fault 67N Transient earth fault 67NI

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Capacitor bank unbalance 2  
 Broken conductor 46 I2/I1  
 Cold load pick-up  
 Switch ON to fault (SOTF)  
 H2 detection  
 H5 detection  
 Breaker failure 50BF  
 Directional active underpower 37P  
 Fault locator 21FL  
 Recloser 79  
 Negative sequence overcurrent 46  
 Overvoltage 59  
 Undervoltage 27  
 Earth fault overvoltage 59N  
 Underfrequency 81/81N  
 Rate of change of frequency 81R  
 Synchro-check 25  
 Lockout relay 86  
 CT supervision  
 VT supervision  
 Programmable stages 99  
 Programmable curve

Measurement functions	Current 3-phase Current zero sequence Current positive sequence Current negative sequence Current ratio of negative and positive Phasor diagram of currents or voltages Current 2nd, 15th harmonics with THD Voltage 3-phase Voltage residual Voltage zero sequence Voltage positive sequence Voltage negative sequence Frequency
Control functions	Switchgear control and monitoring Programmable switchgear interlocking Local/remote control
Controllable switchgear devices	6 controlled + 2 monitored objects
Number of setting groups	4
Monitoring functions	Trip circuit supervision 74 Circuit breaker monitoring Relay self-monitoring
Logs and records	Event recording Disturbance recording Tripping context Relay maintenance
Switchgear diagnosis type	CT/VT supervision ANSI code: 60 Trip circuit supervision ANSI code: 74
Connections - terminals	Screw (digital input/output) Ring lugs (analog inputs and outputs)

## Complementary

Time synchronisation protocol	SNTP
Web server	Embedded HTTP server
Software name	EcoStruxure Power Device ESetup Easergy Pro: virtual simulation test
Number of key	7 customizable
Local signalling	LED 4 LED 10 tri-colour programmable
Height	176 mm
Width	152 mm
Depth	219 mm
Net weight	3.5 kg

## Environment

Electromagnetic compatibility	<p>Emission tests class A conforming to CISPR 11  Emission tests class A conforming to CISPR 22  Emission tests conforming to IACS E10  EMC immunity class 4 conforming to IEC 61000-4-2  EMC immunity class 4 conforming to ANSI C37.90.3  EMC immunity level 3 conforming to IEC 61000-4-3  EMC immunity conforming to ANSI C37.90.2  EMC immunity conforming to GOST 32137  EMC immunity conforming to GOST 30804.4.3  EMC immunity conforming to IACS E10  EMC immunity level 5 conforming to IEC 61000-4-8  EMC immunity level 5 conforming to IEC 61000-4-9  EMC immunity level 5 conforming to IEC 61000-4-10  EMC immunity level 3 conforming to IEC 61000-4-6  EMC immunity level 3 conforming to IEC 61000-4-18  EMC immunity conforming to ANSI C37.90.1  EMC immunity conforming to IEC 61000-4-12  EMC immunity conforming to GOST 30804.4.12  EMC immunity level 4 conforming to IEC 61000-4-16  EMC immunity level 4 conforming to IEC 61000-4-4  EMC immunity level 4 conforming to IEC 61000-4-5</p>
Mechanical robustness	<p>Vibrations (level: class 2) conforming to IEC 60255-21-1  Vibrations conforming to GOST 17516.1  Vibrations conforming to IACS E10  Shocks (level: class 2) conforming to IEC 60255-21-2  Earthquakes (level: class 2) conforming to IEC 60255-21-3</p>
Climatic withstand	<p>Exposure to cold conforming to IEC 60068-2-1  Exposure to dry heat conforming to IEC 60068-2-2  Exposure to damp heat in service conforming to IEC 60068-2-78  Exposure to damp heat in service conforming to IEC 60068-2-30  Temperature variation conforming to IEC 60068-2-14  Salt mist conforming to IEC 60068-2-52  Influence of corrosion/gas test 2 conforming to IEC 60068-2-60  Influence of corrosion/gas test 4 conforming to IEC 60068-2-60  Influence of corrosion/gas test 2 conforming to IEC 60721-3-3  Influence of corrosion/gas test 4 conforming to IEC 60721-3-3</p>
Ambient air temperature for operation	<p>-40...85 °C ( 16 h )  -40...70 °C ( 96 h )</p>
Ambient air temperature for storage	-40...85 °C
IP degree of protection	IP54 conforming to IEC 60529
Relative humidity	<p>0...93 % at 40 °C, without condensation, 56 days  93...95 % at 25...55 °C, 6 cycles, 12 + 12 hours</p>
Maximum operating altitude	2000 m
Protective treatment	<p>Conformal coating conforming to IEC 60068-2-52:Kb/1  Conformal coating conforming to IEC 60068-2-60:Ke  Conformal coating conforming to IEC 60721-3-3:3C2</p>

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	4.5 kg
Package 1 Height	30 cm
Package 1 width	30 cm
Package 1 Length	35 cm

## Offer Sustainability

EU RoHS Directive	<p>Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a></p>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Contractual warranty**

Warranty	Up to 10 years extended warranty (Standard warranty 2 years. Please check with your local SE representative for extended warranty availability and conditions)
----------	--

