



Powering Business Worldwide

pe.eaton.com

M-Max Series Adjustable Frequency AC Drives Basic Controller

MMX34AA5D6F0-0

UPC:786685268828

Dimensions:

- **Height:** 4 IN
- **Length:** 3.54 IN
- **Width:** 7.68 IN

Weight:1.54 LB

Notes:Horsepower ratings are based on the use of a 240V, 460V, and 575V NEMA B, four- or six-pole squirrel cage induction motor and are for reference only.

Warranties:

- 2 year

Specifications:

- **Input Current:** 7.3 A
- **Output Current:** 5.6 A
- **Frame Size:** FS2
- **Horsepower:** 3 hp
- **Phase:** Three-phase in, three-phase out
- **Rating:** IP20
- **Special Features:** AA software design series, EMC filter
- **Type:** Full version
- **Voltage Rating:** 380-480V, 460V

Supporting documents:

- [Variable frequency drive - Product overview](#)
- [Eaton's Volume 6-Solid-State Motor Control](#)
- [MMX_\(FR2\) 2D Drawing Xchange](#)
- [MMX_\(FR2\) AutoCAD 2D Footprint \(mm\)](#)
- [MMX_\(FR2\) 2D PDF](#)
- [MMX_\(FR2\) 3D Model Xchange](#)



- [MMX_\(FR2\) 3D Inventor](#)
- [MMX_\(FR2\) AutoCAD 2D Footprint](#)
- [User Manual, M-Max Series Adjustable Frequency Drive](#)
- [M-Max Series adjustable frequency drives](#)
- [Eaton Specification Sheet - MMX34AA5D6F0-0](#)

Certifications:

- EN 61800-5-1
- cUL Certified
- EN 61800-3
- UL Listed
- EN 60204-1

Product compliance:

- RoHS Compliant
- EMC Category C2, C3, and C4 (Level H): With an internal RFI filter option
- CE Marked