



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8288-1DB10-1BW1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Δ	ALM 400V	130.0	2,481.0	245.0	395	17.0	500	6,550	650.0	3,300	2,481.0	245	0.941	0.82	127.0
	BLM/SLM 400V	103.0	2,459.0	245.0	325	13.6	400	6,550	650.0	3,300	2,459.0	245	0.931	0.80	136.0
	ALM/BLM/SLM 480V	155.0	2,474.0	245.0	460	20.3	600	6,550	650.0	3,300	2,474.0	245	0.948	0.84	121.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	280
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	53 min
Moment of inertia	63,000 kgcm ²
Weight (approx.)	1,650 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	1XB7700-P02

Cooling data and sound pressure level

Airflow, min.	0.42 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	74 dB ¹⁾
Air discharge	radial
Pressure drop	600 Pa

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3300 rpm