



Figure similar

### MLFB-Ordering data

6SL3210-5DE24-0UA0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

### Rated data

#### Input

Number of phases	3 AC
Line voltage	380 ... 480 V -15 % +10 %
Line frequency	45 ... 66 Hz

#### Output

Rated power	15.00 kW
Rated current (IN)	37.60 A
Max. output current	75.20 A

#### Electronic power supply

Power supply	24 V ±10 %
--------------	------------

### General tech. specifications

Power loss	400.00 W
------------	----------

### Connections

#### Motor end

Conductor cross-section	16.0 mm <sup>2</sup>
-------------------------	----------------------

### Mechanical data

Degree of protection	IP20 / UL open type
Size	FSD
Net weight	8.30 kg ( 18.30 lb )
Width	190.0 mm ( 7.48 in )
Height	350.0 mm ( 13.78 in )
Depth	185.0 mm ( 7.28 in )

### Ambient conditions

Cooling	Forced-air cooling via fan
---------	----------------------------

Installation altitude	1000 m
-----------------------	--------

Cooling air requirement	0.005 m <sup>3</sup> /s ( 0.177 ft <sup>3</sup> /s )
-------------------------	--

#### Ambient temperature

Operation	0 ... 45 °C (32 ... 113 °F)
-----------	-----------------------------

Storage	-40 ... 70 °C (-40 ... 158 °F)
---------	--------------------------------

Transport	-40 ... 70 °C (-40 ... 158 °F)
-----------	--------------------------------

#### Relative humidity

Max. operation	90 %
----------------	------

### Standards

Compliance with standards	CE
---------------------------	----