

MLFB-Ordering data

6SL3220-3YH58-1CB0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data			General tech. specifications	
Input			Power factor λ	0.75 ... 0.93
Number of phases	3 AC		Offset factor $\cos \varphi$	0.96
Line voltage	500 ... 690 V +10 % -10 %		Efficiency η	0.98
Line frequency	47 ... 63 Hz		Sound pressure level (1m)	74 dB
Rated voltage	690V IEC	600V NEC	Power loss	6.191 kW
Rated current (LO)	401.00 A	408.00 A	Filter class (integrated)	RFI suppression filter for Category C3
Rated current (HO)	327.00 A	333.00 A		
Output			EMC category (with accessories)	Category C3
Number of phases	3 AC		Ambient conditions	
Rated voltage	690V IEC	600V NEC	Standard board coating type	Class 3C2, according to IEC 60721-3-3: 2002
Rated power (LO)	355.00 kW	400.00 hp	Cooling	Air cooling using an integrated fan
Rated power (HO)	315.00 kW	300.00 hp	Cooling air requirement	0.362 m³/s (12.784 ft³/s)
Rated current (LO)	385.00 A	388.00 A	Installation altitude	1000 m (3280.84 ft)
Rated current (HO)	314.00 A	320.00 A	Ambient temperature	
Rated current (IN)	400.00 A		Operation	0 ... 45 °C (32 ... 113 °F)
Max. output current	529.00 A		Transport	-40 ... 70 °C (-40 ... 158 °F)
Pulse frequency	2 kHz		Storage	-25 ... 55 °C (-13 ... 131 °F)
Output frequency for vector control	0 ... 100 Hz		Relative humidity	
Output frequency for V/f control	0 ... 100 Hz		Max. operation	95 % At 40 °C (104 °F), condensation and icing not permissible

Overload capability

Low Overload (LO)

110% base load current IL for 60 s in a 300 s cycle time

High Overload (HO)

150% x base load current IH for 60 s within a 600 s cycle time



Figure similar

Mechanical data

Degree of protection	IP20 / UL open type
Size	FSH
Net weight	158 kg (348.33 lb)
Width	548 mm (21.57 in)
Height	1695 mm (66.73 in)
Depth	393 mm (15.47 in)

Inputs / outputs

Standard digital inputs

Number	6
Switching level: 0→1	11 V
Switching level: 1→0	5 V
Max. inrush current	15 mA

Fail-safe digital inputs

Number	1
--------	---

Digital outputs

Number as relay changeover contact	2
Output (resistive load)	DC 30 V, 5.0 A
Number as transistor	0

Analog / digital inputs

Number	2 (Differential input)
Resolution	10 bit

Switching threshold as digital input

0→1	4 V
1→0	1.6 V

Analog outputs

Number	1 (Non-isolated output)
--------	-------------------------

PTC/ KTY interface

1 motor temperature sensor input, sensors that can be connected: PTC, KTY and Thermo-Click, accuracy ±5 °C

Closed-loop control techniques

V/f linear / square-law / parameterizable	Yes
V/f with flux current control (FCC)	Yes
V/f ECO linear / square-law	Yes
Sensorless vector control	Yes
Vector control, with sensor	No
Encoderless torque control	Yes
Torque control, with encoder	No

Communication

Communication	USS, Modbus RTU, BACnet MS/TP
---------------	-------------------------------

Connections

Signal cable

Conductor cross-section	0.15 ... 1.50 mm ² (AWG 24 ... AWG 16)
-------------------------	--

Line side

Version	M12 screw
Conductor cross-section	240.00 mm ² (MCM 2 x 500 ... MCM 4 x 500)

Motor end

Version	M12 screw
Conductor cross-section	240.00 mm ² (MCM 2 x 500 ... MCM 4 x 500)

DC link (for braking resistor)

PE connection	M12 screw
---------------	-----------

Max. motor cable length

Shielded	150 m (492.13 ft)
----------	-------------------



Figure similar


Converter losses to EN 50598-2*

Efficiency class

IE2

Comparison with the reference converter (90% / 100%)

-34.60 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency (f). The values are valid for the basic version of the converter without options/components.

*converted values

Standards

Compliance with standards

UL, cUL, CE, C-Tick (RCM), EAC, KCC, SEMI F47, REACH

CE marking

EMC Directive 2004/108/EC, Low-Voltage Directive 2006/95/EC

Operator panel: Intelligent Operator Panel (IOP-2)

Screen

Display design

LCD colors

Screen resolution

320 x 240 Pixel

Ambient conditions

Ambient temperature during

Operation

0 ... 50 °C (32 ... 122 °F)

55 °C only with door mounting kit

Storage

-40 ... 70 °C (-40 ... 158 °F)

Transport

-40 ... 70 °C (-40 ... 158 °F)

Mechanical data

Degree of protection

IP55 / UL type 12

Net weight

0.13 kg (0.30 lb)

Width

70.0 mm (2.76 in)

Height

106.85 mm (4.21 in)

Depth

19.65 mm (0.77 in)

Relative humidity at 25°C during

Max. operation

95 %

Approvals

Certificate of suitability

CE, cULus, EAC, KCC, RCM

I/O Extension Module

Technical specifications for the I/O Extension Modul are available via direct input (MLFB 6SL3255-0BE00-0AA0).