Product data sheet
Characteristics

9070SK1000G1D1G13P1
Transformer Control Disconnect 1kVA

Main

Device short name	SK
Enclosure type	Standard environment enclosure indoor
Product or Component Type	Power supply source
Provided equipment	Vario V3 switch-disconnector
Range of Product	Square D

Complementary

Depth	8.96 in (227.58 mm)
Design	Standard
Device mounting	Surface
Electrical connection	Screw clamp terminal
Height	9.4 in (238.76 mm)
Material	Copper winding
Mounting support	Panel
Phase	1 phase
Primary Voltage	240 x 480 V
Rated power in VA	1000 VA
Rated voltage	120 V auxiliary power supply 120 V isolated
Secondary Voltage	120 V
Temperature rise	115 °C
Width	11.8 in (299.72 mm)

Environment

Insulation temperature	356 °F (180 °C)
NEMA Degree of Protection	NEMA 1
Product Certifications	UL listed file E61239 CSA LR37055 CE

Ordering and shipping details

Category	21694-9070 SK
Discount Schedule	CP8
GTIN	00785901058663
Returnability	No

Schneider Electric
9070SK1000G1D1G13P1 | Visit gesrepair.com for product support.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months