

## Product data sheet

### Characteristics

# 8940XSG4200V06

Pump Panel, NEMA Type S, Well Guard,  
Size 5, 270A, 200 HP, LLL36600U31X circuit  
breaker, Motor Logic SSOLR, 440/480 VAC  
50/60 Hz coil, NEMA 3R



### Main

Product	Well-Guard Control
Type	Class 8940 type X
Device application	Pumping

### Complementary

Control Circuit Type	Common control circuit
Control Circuit Voltage	480 V AC 60 Hz 440 V AC 50 Hz
Line Rated Current	270 A
Number of Poles	3
Horsepower Rating	200 hp 480 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO) Push-button START)
Disconnect Type	Associated circuit breaker
Circuit breaker CT rating	400 A
Circuit breaker type	LLL
Thermal overload type	Motor Logic solid state class 10/20
Protection Type	Overload Phase loss Phase unbalance
Device mounting	Surface
Electrical Connection	Screw terminal
NEMA size	5
Height	74.49 in (1892 mm)
Width	23.50 in (597 mm)
Depth	17.56 in (446 mm)

### Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product certifications	UL Listed NEMA


SQUARE D 8940XSG4200V06 | Visit

gesrepair.com for product support.

## Ordering and shipping details

Category	21392-8940 NSG,XS
Discount Schedule	CP1
GTIN	785901176732
Nbr. of units in pkg.	1
Package weight(Lbs)	2.20 lb(US) (1.000 kg)
Returnability	Yes
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Under investigation
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------