8940SSF4100V02S

Pump Panel, NEMA Type S, Well Guard, Size 4, 135A, 10kA SSCR, 100HP, 200A Class H and K fuse clip, Motor Logic SSOLR, 120VAC 60Hz coil, NEMA 3R



Main		
Product	Well-Guard Control	
Туре	Class 8940 type SS	
Device application	Pumpina	

Complementary

o ciripionian y		
Control Circuit Type	Separate control circuit	
Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz	
Line Rated Current	135 A	
Number of Poles	3	
Horsepower Rating	100 hp 480 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Control Units	Selector switch HAND-OFF-AUTO) Push-button START)	
Disconnect Type	Fusible disconnect switch	
Associated fuse rating	200 A	
Fuse type	H or K	
Thermal overload type	Motor Logic solid state class 10/20	
Protection Type	Overload Phase loss Phase unbalance	
Device mounting	Surface	
Electrical Connection	Screw terminal	
NEMA size	4	
Height	49.02 in (1245 mm)	
Width	20.55 in (522 mm)	
Depth	10.35 in (263 mm)	

Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product certifications	UL Listed NEMA

Square D 8940SSF4100V02S | Visit

Ordering and shipping details

Category	21389-8940 NSE,NSF	
Discount Schedule	CP1	
GTIN	785901147497	
Nbr. of units in pkg.	1	
Package weight(Lbs)	147.00 lb(US) (66.678 kg)	
Returnability	Yes	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	13.39 in (34 cm)	
Package 1 width	29.80 in (75.7 cm)	
Package 1 Length	39.49 in (100.3 cm)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	6	
Package 2 Weight	920.83 lb(US) (417.68 kg)	
Package 2 Height	40.00 in (101.6 cm)	
Package 2 width	45.00 in (114.3 cm)	
Package 2 Length	51.00 in (129.54 cm)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS Declaration	
PVC free	Yes	

Contractual warranty

Warranty	18 months