# Product data sheet
## Characteristics

# H365SS
Safety switch, heavy duty, fusible, 400A, 3 poles, 250 hp, 600 VAC/600 NDC, NEMA 4, 4X, 5, 316 steel,

## Main

| | |
|---|---|
| Product | Single Throw Safety Switch |
| Duty Rating | Heavy duty |
| Device application | Heavy application |
| Disconnect Type | Fusible disconnect |
| Factory Installed Neutral | None |
| Phase | 3 phase |
| Number of Poles | 3 |
| Current Rating | 400 A |
| Voltage Rating | 600 V AC/DC |
| Enclosure Rating | NEMA 4/4X/5 stainless steel 316 |
| Maximum Horse Power Rating | 100 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6<br>250 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52<br>125 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6<br>350 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52<br>50 hp 600 V at DC |

## Complementary

| | |
|---|---|
| Mounting Type | Surface |
| Wiring configuration | 3-wire |
| Wire Size | AWG 1/0...750 kcmil copper or aluminium |
| Tightening torque | 550 lbf.in (62.14 N.m) (AWG 1/0...750 kcmil) |
| Depth | 9.75 in (247.65 mm) |
| Width | 26.25 in (666.75 mm) |
| Height | 48 in (1219.20 mm) |

## Environment

| | |
|---|---|
| Certifications | UL listed file E2875 |

## Ordering and shipping details

| | |
|---|---|
| Category | 00010-H&HU SW,2&3P,N4,SS,30-200A |
| Discount Schedule | DE1 |
| GTIN | 3606481243904 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 175 lb(US) (79.38 kg) |
| Returnability | No |
| Country of origin | MX |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Square D H365SS | Visit gesrepair.com for product support.

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |