



Main

Product or Component Type	Shunt trip
Circuit breaker type	H-frame L-Frame J-frame

Complementary

Rated voltage	110...130 V AC
Tightening torque	12.39 lbf.in (1.4 N.m) 0.00...0.00 in ² (0.82...2.5 mm ²) (AWG 18...AWG 14)

Environment

Product Certifications	CSA
------------------------	-----

Ordering and shipping details

Category	01103-H,J,COMPACT NS UL/IEC CIRCUIT BREAKER ACCESSORIES
Discount Schedule	DE2
GTIN	3606485955865
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.80 in (4.572 cm)
Package 1 Width	4.20 in (10.668 cm)
Package 1 Length	5.70 in (14.478 cm)
Package 1 Weight	5.28 oz (149.685 g)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. Only such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.