QOU3501200

Mini circuit breaker, QOU, 50A, 3 pole, 240 VAC, 10kA, auxiliary switch







Main	
Product or Component Type	Miniature circuit-breaker
Range of Product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR rated

C			
Com	nien	iemia	IIV
00111	p. 0		,

Line Rated Current	50 A
Electrical connection	Slotted box lugs, line side
	Slotted box lugs, load side
[Ue] rated operational voltage	120/240 V AC
	240 V AC
	120 V AC
	48 V DC
Mounting Mode	Unit mount
AWG gauge	AWG 14AWG 2 aluminium/copper
Height	4.05 in (102.87 mm)
Width	3 in (76.20 mm)
Depth	2.95 in (74.93 mm)
Tightening torque	45 lbf.in (5.08 N.m) (AWG 14AWG 2)

Environment

LIMIGITICIT	
Product Certifications	IEC
	UL Listed
	CSA

Ordering and shipping details

Category	00900-QOU BREAKERS & SWITCH
Discount Schedule	DE2
GTIN	00785901120803
Returnability	No
Country of origin	MX

Packing Units

3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.05 in (10.287 cm)	
Package 1 Width	2.96 in (7.518 cm)	
Package 1 Length	3.03 in (7.696 cm)	
Package 1 Weight	11.36 oz (322.051 g)	

Square D QOU3501200 Circuit Protection

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	[™] China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Halogen content performance	Halogen free product	

Contractual warranty

Warranty 18 months	
Warranty 18 months	
To months	