SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : 1PH8105-1SS00-0LA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
Y	**ALM 400V**	**10.0**	**48.0**	**23.0**	**366**	**68.9**	**2,000**	**100**	**46.0**	**12,000**	**55.0**	**25**	**0.891**	**0.800**	**10.9**
	BLM/SLM 400V	7.5	48.0	23.0	285	52.1	1,500	100	46.0	12,000	55.0	25	0.864	0.790	11.5
	ALM 480V	14.5	46.0	22.8	495	102.7	3,000	100	46.0	12,000	55.0	25	0.910	0.830	10.9
	BLM/SLM 480V	12.5	48.0	23.0	451	85.5	2,500	100	46.0	12,000	55.0	25	0.922	0.800	10.9
Δ	**ALM 400V**	**9.3**	**18.0**	**24.0**	**398**	**168.0**	**5,000**	**65**	**86.0**	**12,000**	**36.0**	**34**	**0.914**	**0.710**	**13.2**
	BLM/SLM 400V	7.5	18.0	24.0	308	134.6	4,000	65	86.0	12,000	36.0	35	0.907	0.730	12.7
	ALM 480V	13.0	18.0	22.0	500	234.9	7,000	65	86.0	12,000	36.0	35	0.920	0.760	12.7
	BLM/SLM 480V	11.2	18.0	22.0	460	201.3	6,000	65	86.0	12,000	36.0	35	0.932	0.730	12.7

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	100
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	SPECIAL/B
Shaft and flange accuracy	SPECIAL
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Performance
Shaft end	Plain shaft
Encoder system	Incremental encoder 19 bit without commutation position (encoder IN19DQ)

Physical constants

Thermal time constant	20 min
Moment of inertia	252 kgcm²
Weight (approx.)	65 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk826

Cooling data and sound pressure level

Airflow, min.	0.04 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB [1]
Air discharge	axial
Pressure drop	110 Pa

External fan

Max. power consumption	
3 AC 400 V / 50 Hz (±10%)	0.10 A
3 AC 400 V / 60 Hz (±10%)	0.08 A
3 AC 480 V / 60 Hz (±10%)	0.11 A

[1] at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Siemens 1PH81051SS000LA1 Motors and Motor Control | gesrepair.com