SIEMENS

Data sheet 1PH8107-1DD13-0LB1-Z X01

	SIMOTICS M compact asynchronous motor 1000 rpm 6.3 kW 60 Nm 17.5 A 307 V 1150 rpm 7.2 kW 60 Nm 17.5 A 348 V 1350 rpm 8 kW 57 Nm 17 A 400 V 1500 rpm 8.8 kW 56 Nm 17 A 440 V forced ventilation; direction of air flow NDE--> DE; IP55 degree of protection Incremental encoder 22-bit with commutation position (encoder IC22DQ) with DRIVE-CLiQ interface Design IM B35 (IM V15, (IM V35) PLAIN SHAFT WITHOUT FITTED KEY; BEARING: PERFORMANCE, VIBRATION SEVERITY GRADE SPECIAL/B; SHAFT A. FLANGE ACCURACY GR. SPECIAL TERMINAL BOX (ABOVE) CABLE ENTRY ON THE LEFT SIGNAL CONNECTION D-END X01: Standard paint finish in RAL 9005 (matte black)

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens