SIEMENS

## Data sheet for SIMOTICS M-1PH8



Figure similar

**Article No. :** 1PH8107-1FD03-1BH1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

### Engineering data

| | | $P_N$ [kW] | $M_N$ [Nm] | $I_N$ [A] | $U_N$ [V] | $f_N$ [Hz] | $n_N$ [rpm] | $M_{max}$ [Nm] | $I_{max}$ [A] | $n_{max}$ [rpm] | $M_0$ [Nm] | $I_0$ [A] | η | cos φ | Iμ [A] |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Y | **ALM 400V** | **7.2** | **60.0** | **17.5** | **348** | **40.6** | **1,150** | **135** | **40.0** | **9,000** | **63.0** | **25** | **0.852** | **0.820** | **8.2** |
| | BLM/SLM 400V | 6.3 | 60.0 | 17.5 | 307 | 35.5 | 1,000 | 135 | 40.0 | 9,000 | 63.0 | 25 | 0.834 | 0.820 | 8.2 |
| | ALM 480V | 8.8 | 56.0 | 17.0 | 440 | 52.0 | 1,500 | 135 | 40.0 | 9,000 | 63.0 | 25 | 0.870 | 0.800 | 8.2 |
| | BLM/SLM 480V | 8.0 | 57.0 | 17.0 | 400 | 47.1 | 1,350 | 135 | 40.0 | 9,000 | 63.0 | 25 | 0.867 | 0.800 | 8.2 |

### Mechanical data

| | |
|---|---|
| Motor type | Squirrel cage asynchronous motor |
| Shaft height | 100 |
| Cooling | Forced ventilation DE -> NDE |
| Vibration severity grade | R/A |
| Shaft and flange accuracy | R |
| Degree of protection | IP55 |
| Design acc. to Code I | IM B35 (IM V15, IM V35) |
| Temperature monitoring | Pt1000 temperature sensor in the stator winding |
| Color | Standard (Anthracite RAL 7016) |
| Type of the bearing | Standard with fixed bearing |
| Shaft end | Feather key with full key balancing |
| Encoder system | Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm |

### Physical constants

| | |
|---|---|
| Thermal time constant | 20 min |
| Moment of inertia | 289 kgcm² |
| Weight (approx.) | 73 kg |

### Connection

| | |
|---|---|
| Type of electrical connection | Power connector |
| Position of the connection | Power connector, top |
| Power connection | DE |
| Signal connection | left |

### Cooling data and sound pressure level

| | |
|---|---|
| Airflow, min. | 0.04 m³/s |
| Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB | 70 dB [1] |
| Air discharge | axial |
| Pressure drop | 110 Pa |

### External fan

**Max. power consumption**

| | |
|---|---|
| 3 AC 400 V / 50 Hz (±10%) | 0.10 A |
| 3 AC 400 V / 60 Hz (±10%) | 0.08 A |
| 3 AC 480 V / 60 Hz (±10%) | 0.11 A |

[1] at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Siemens 1PH81071FD031BH1 Motors and Motor Control | gesrepair.com