SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : 1PH8137-1SD02-3MA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	Iμ [A]
Y	**ALM 400V**	**19.5**	**162.0**	**43.0**	**350**	**39.9**	**1,150**	**405**	**108.0**	**12,000**	**176.0**	**45**	**0.891**	**0.880**	**16.1**
	BLM/SLM 400V	17.0	162.0	43.0	307	34.8	1,000	405	108.0	12,000	176.0	45	0.881	0.880	15.1
	ALM 480V	24.0	153.0	41.0	447	51.5	1,500	405	108.0	12,000	176.0	45	0.890	0.860	15.9
	BLM/SLM 480V	22.0	156.0	42.0	404	46.4	1,350	405	108.0	12,000	176.0	45	0.902	0.860	15.9

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	SPECIAL/B
Shaft and flange accuracy	SPECIAL
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	High Performance
Shaft end	Smooth hollow shaft
Encoder system	Incremental encoder 19 bit without commutation position (encoder IN19DQ)

Physical constants

Thermal time constant	30 min
Moment of inertia	1,090 kgcm²
Weight (approx.)	141 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

Cooling data and sound pressure level

Airflow, min.	0.09 m³/s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB [1]
Air discharge	axial
Pressure drop	140 Pa

External fan

Max. power consumption

3 AC 400 V / 50 Hz (±10%)	0.10 A
3 AC 400 V / 60 Hz (±10%)	0.12 A
3 AC 480 V / 60 Hz (±10%)	0.12 A

[1] at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Siemens 1PH81371SD023MA1 Motors and Motor Control | gesrepair.com