SIEMENS

Data sheet for SIMOTICS M-1PH8



Figure similar

Article No. : 1PH8138-1DF20-1CA1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P_N [kW]	M_N [Nm]	I_N [A]	U_N [V]	f_N [Hz]	n_N [rpm]	M_{max} [Nm]	I_{max} [A]	n_{max} [rpm]	M_0 [Nm]	I_0 [A]	η	cos φ	I_μ [A]
Y	**ALM 400V**	**33.0**	**180.0**	**77.0**	**332**	**60.1**	**1,750**	**400**	**168.0**	**8,000**	**223.0**	**88**	**0.898**	**0.870**	**27.1**
	BLM/SLM 400V	30.0	191.0	80.0	289	51.9	1,500	400	168.0	8,000	223.0	88	0.882	0.880	27.1
	ALM 480V	39.0	169.0	72.0	410	75.0	2,200	400	168.0	8,000	223.0	88	0.910	0.860	28.4
	BLM/SLM 480V	37.0	177.0	76.0	380	68.4	2,000	400	168.0	8,000	223.0	88	0.920	0.860	28.4

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Water cooling
Vibration severity grade	S/A
Shaft and flange accuracy	R
Degree of protection	IP65
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft end	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

Physical constants

Thermal time constant	12 min
Moment of inertia	1,090 kgcm²
Weight (approx.)	157 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

Cooling data and sound pressure level

Flow rate, min.	12 l/min
Sound pressure level LpA(1m) motor rated load, tolerance + 3dB	68 dB [1]
Pressure drop	0.9 bar
NDE thread connection	0.375 Inches

Cooling water specification

pH value	6 ... 9
Total hardness	1.7 mmol/l
Electrical conductivity	500 µS/cm
Chloride ions	40 mg/l
Sulfate ions	50 mg/l
Nitrate ions	50 mg/l
Dissolved substances	340 mg/l
Maximum particle size	100 µm
Antifreeze/corrosion protection	20 ... 30 %

[1] at a rated frequency of 4 kHz and a speed range of up to 5000 rpm

Siemens 1PH81381DF201CA1 Motors and Motor Control | gesrepair.com