SIEMENS

Data sheet 1PH8184-1FF10-1FC1-Z G14

	SIMOTICS M Compact induction motor 1500rpm, 51kW 325Nm, 116A, 335V 1750rpm, 60kW 327Nm, 120 A, 390V 2000rpm, 68kW 325Nm, 118A, 405V forced ventilation Direction of air flow NDE-->DE Degree of protection IP55 Absolute encoder 22-bit Single-turn and 12-bit multi-turn (encoder AM22DQ) with DRIVE-CLiQ interface DESIGN IM B3 (IMB6, IMB7, IMB8, IMV6) SHAFT WITH FITTED KEY FULL-KEY BALANCING BEARING: GREATER CANTILEVER FORCES; VIBRATION SEVERITY GRADE R/A; SHAFT AND FLANGE ACCURACY GR. R TERMINAL BOX (ABOVE) CABLE ENTRY ON THE ND-END SIGNAL CONNECTION RIGHT G14: FAN ASSEMBLY WITH AIR FILTER

Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)
https://support.industry.siemens.com/cs/products?mfn=ps&lc=en-WW

Industry Mall (Online ordering system)
https://mall.industry.siemens.com

Subject to change without notice
© Copyright Siemens